

Colour Range





















Kenross

Technical Information

		Translucent		Blockou	ut	
	Composition:	100% Polyester with Clear Acrylic Coating		100% Polyester with Clear Acrylic Coating		
	Thickness:	0.50mm ± 10%		0.68mm ± 10%		
	Weight:	240 gsm ± 10%		450 gsm ± 10%		
	Cutting*:	Ultrasonic Cut		Ultrasonic Cut		
	Colourfastness:	6-7 Blue Scale (AS 2001.4.21)				
	Fire Retardancy Information for NON FR Products^:	Suitable for all building classes <u>except</u> Class 9(b) entertainment venues. A summary of BCA requirements can be provided on request.				
	TOTAL TOTAL OF THE PARTY OF THE	$^{\wedge}$ Fabrics which are not FR treated, have been FR tested and have a Flammability result over 6 or fabrics which are not FR treated and have not undergone FR testing.				
	Range:	Item:	Width	:	Roll Length:	
		Translucent - 60010300090XXH	3000mm		30 metres	
		Blockout - 60011300090XXH	3000mm		25 metres	
	Care & Cleaning	Dusting with a feather duster is all that is required to be fabric looking good. For the removal of stains, dirt and wipe fabric skins with a sponge soaked in lukewarm ware still visible, add a little detergent. Then dry gently cloth. Test in inconspicuous area before spot cleaning				