

## **Colour Range**

















Internal Translucent & Blockout Fabric

## Scarborough

## **Technical Information**

Tranc	lucent
II aliə	ucent

nt Blockout

Composition: 100% Polyester with Clear Acrylic Coating

100% Polyester with Acrylic Foam Coating

 Thickness:
 0.75mm ± 10%

 Weight:
 250 gsm ± 10%

 Cutting\*:
 Ultrasonic Cut

 $0.80 \text{mm} \pm 10\%$  $455 \text{ gsm} \pm 10\%$ 

utting\*: Ultrasonic Cut Knife, Crush or Pressure Cut

Colourfastness: 6-7 Blue Scale (AS 2001.4.21)
Features: Proudly Made in Australia

Fire Retardancy Information for NON FR Products^: Suitable for all building classes <u>except</u> Class 9(b) entertainment venues. A summary of BCA requirements can be provided on request. ^ Fabrics which are not FR treated, have been FR tested and have a Flammability result over 6 or fabrics which are not FR treated and have not undergone FR testing.

 Range:
 Item:
 Width:
 Roll Length:

 Translucent - 8SCA300XXH
 3000mm
 30 metres

 Blockout - 8SCA3300XXH
 3000mm
 25 metres

Care & Cleaning

Dusting with a feather duster is all that is required to keep your fabric looking good. For the removal of stains, dirt and grime, gently wipe fabric skins with a sponge soaked in lukewarm water. If marks are still visible, add a little detergent. Then dry gently with a clean cloth. Test in inconspicuous area before spot cleaning.